

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C11D 7/50, D06L 1/02	A1	(11) International Publication Number: WO 97/22683 (43) International Publication Date: 26 June 1997 (26.06.97)
(21) International Application Number: PCT/US96/07157 (22) International Filing Date: 17 May 1996 (17.05.96) (30) Priority Data: 08/573,416 15 December 1995 (15.12.95) US (71) Applicant: MINNESOTA MINING AND MANUFACTURING COMPANY [US/US]; 3M Center, P.O. Box 33427, Saint Paul, MN 55133-3427 (US). (72) Inventors: FLYNN, Richard, M.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). MOORE, George, G., I.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). GRENFELL, Mark, W.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). OWENS, John, G.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). MILBRATH, Dean, S.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). (74) Agents: SCHULTE, Daniel, C. et al.; Minnesota Mining and Manufacturing Company, Office of Intellectual Property Counsel, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: CLEANING PROCESS AND COMPOSITION (57) Abstract A process for removing contaminants from the surface of a substrate comprises contacting the substrate with a cleaning composition comprising at least one mono-, di-, or trialkoxy-substituted perfluoroalkane, perfluorocycloalkane, perfluorocycloalkyl-containing perfluoroalkane, or perfluorocycloalkylene-containing perfluoroalkane compound, the compound optionally containing additional catenary heteroatoms. The compounds exhibit good solvency properties while being environmentally acceptable.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

CLEANING PROCESS AND COMPOSITION

5 This application is a continuation-in-part of
Application No. 08/573,416 filed December 15, 1995.

Field of the Invention

 This invention relates to cleaning
10 compositions comprising at least one partially-
fluorinated ether compound and to processes for
removing contaminants from substrate surfaces using
such compositions. In another aspect, this invention
relates to certain novel partially-fluorinated ether
15 compounds. In yet another aspect, this invention
relates to coating compositions comprising at least one
partially-fluorinated ether compound and to processes
for depositing coatings on substrate surfaces using
such compositions.

20

Background of the Invention

 Solvent cleaning applications where
contaminated articles are immersed in (or washed with)
solvent liquids and/or vapors are well-known..
25 Applications involving one or more stages of immersion,
rinsing, and/or drying are common. Solvents can be
used at ambient temperature (often, accompanied by
ultrasonic agitation) or at elevated temperatures up to
the boiling point of the solvent.
30 A major concern in solvent cleaning is the
tendency (especially where solvent is used at an

elevated temperature) for solvent vapor loss from the cleaning system into the atmosphere. Although care is generally exercised to minimize such losses (e.g., through good equipment design and vapor recovery systems), most practical cleaning applications result in some loss of solvent vapor into the atmosphere.

Solvent cleaning processes have traditionally utilized chlorinated solvents (e.g., chlorofluorocarbons such as 1,1,2-trichloro-1,2,2-trifluoroethane and chlorocarbons such as 1,1,1-trichloroethane) alone or in admixture with one or more cosolvents such as aliphatic alcohols or other low molecular weight, polar compounds. Such solvents were initially believed to be environmentally-benign, but have now been linked to ozone depletion. According to the Montreal Protocol and its attendant amendments, production and use of the solvents must be discontinued (see, e.g., P. S. Zurer, "Looming Ban on Production of CFCs, Halons Spurs Switch to Substitutes," Chemical & Engineering News, page 12, November 15, 1993).

Thus, there has developed a need in the art for substitutes or replacements for the commonly-used cleaning solvents. Such substitutes should have a low ozone depletion potential, should have boiling ranges suitable for a variety of solvent cleaning applications, and should have the ability to dissolve both hydrocarbon-based and fluorocarbon-based soils. Preferably, substitutes will also be low in toxicity, have no flash points (as measured by ASTM D3278-99), have acceptable stability for use in cleaning

applications, and have short atmospheric lifetimes and low global warming potentials.

Partially-fluorinated ethers have been suggested as chlorofluorocarbon alternatives (see, 5 e.g., Yamashita et al., International Conference on CFC and BFC (Halon), Shanghai, China, August 7-10, 1994, pages 55-58).

European Patent Publication No. 0 450 855 A2 (Imperial Chemical Industries PLC) describes the use of 10 low molecular weight, fluorine-containing ethers of boiling point 20-120°C in solvent cleaning applications.

International Patent Publication No. WO 93/11280 (Allied-Signal, Inc.) discloses a non-aqueous cleaning process which utilizes a fluorocarbon- 15 based rinsing solvent.

U.S. Patent No. 5,275,669 (Van Der Puy et al.) describes hydrofluorocarbon solvents useful for dissolving contaminants or removing contaminants from the surface of a substrate. The solvents have 4 to 7 20 carbon atoms and have a portion which is fluorocarbon, the remaining portion being hydrocarbon.

U.S. Patent No. 3,453,333 (Litt et al.) discloses fluorinated ethers containing at least one halogen substituent other than fluorine and states that 25 those ethers which are liquid can be used as solvents for high molecular weight resinous perhalogenated compounds such as solid polychlorotrifluoroethylene resins.

French Patent Publication No. 2,287,432 30 (Societe Nationale des Poudres et Explosifs) describes new partially-fluorinated ethers and a process for

their preparation. The compounds are said to be useful as hypnotic and anesthetic agents; as monomers for preparing heat-stable, fire-resistant, or self-lubricant polymers; and in phyto-sanitary and phyto-pharmaceutical fields.

German Patent Publication No. 1,294,949 (Farbwerke Hoechst AG) describes a technique for the production of perfluoroalkyl-alkyl ethers, said to be useful as narcotics and as intermediates for the preparation of narcotics and polymers.

Summary of the Invention

In one aspect, this invention provides a process for removing contaminants (e.g., hydrocarbons, fluorocarbons, or even water) from the surface of a substrate (e.g., metal, glass, ceramic, plastic, or fabric). The process comprises contacting the substrate with (or exposing the substrate to) a liquid- and/or vapor-phase cleaning composition comprising at least one mono-, di-, or trialkoxy-substituted perfluoroalkane, perfluorocycloalkane, perfluorocycloalkyl-containing perfluoroalkane, or perfluorocycloalkylene-containing perfluoroalkane compound. The compound can optionally contain additional catenary (i.e., in-chain) heteroatoms (e.g., oxygen or nitrogen) and preferably has a boiling point in the range of from about 25°C to about 200°C.

The alkoxy-substituted compounds used in the process of the invention exhibit unexpectedly high stabilities in the presence of acids, bases, and oxidizing agents. In addition, in spite of their

fluorine content, the compounds are surprisingly good solvents for hydrocarbons (as well as fluorocarbons). The compounds are low in toxicity and flammability, have ozone depletion potentials of zero, and have short atmospheric lifetimes and low global warming potentials relative to chlorofluorocarbons and many chlorofluorocarbon substitutes. Since the compounds exhibit good solvency properties while being environmentally acceptable, they satisfy the need in the art for substitutes or replacements for the commonly-used cleaning solvents which have been linked to the destruction of the earth's ozone layer.

In other aspects, this invention also provides certain novel mono-, di-, and trialkoxy-substituted perfluorocompounds; a cleaning composition; a coating composition; and a process for depositing coatings (e.g., coatings of lubricant) on substrate surfaces.

Detailed Description of the Invention

Compounds which can be utilized in the processes of the invention are mono-, di-, or trialkoxy-substituted perfluoroalkane, perfluorocycloalkane, perfluorocycloalkyl-containing perfluoroalkane, and perfluorocycloalkylene-containing perfluoroalkane compounds. The compounds include those which contain additional catenary heteroatoms (as well as those which do not) and can be utilized alone, in combination with one another, or in combination with other common cleaning solvents (e.g., alcohols, ethers, alkanes, alkenes, perfluorocarbons, perfluorinated

tertiary amines, perfluoroethers, cycloalkanes, esters, ketones, aromatics, siloxanes, hydrochlorocarbons, hydrochlorofluorocarbons, and hydrofluorocarbons). The compounds can be solids or liquids under ambient
5 conditions of temperature and pressure, but are generally utilized for cleaning in either the liquid or the vapor state (or both). Thus, normally solid compounds can be utilized after transformation to liquid and/or vapor through melting, sublimation, or
10 dissolution in liquid co-solvent.

A class of useful alkoxy-substituted perfluorocompounds is that which can be represented by the following general formula (I):




wherein x is an integer of 1 to 3; when x is 1, R_f is selected from the group consisting of linear or branched perfluoroalkyl groups having from 2 to about 15 carbon atoms, perfluorocycloalkyl-containing
20 perfluoroalkyl groups having from 5 to about 15 carbon atoms, and perfluorocycloalkyl groups having from 3 to about 12 carbon atoms; when x is 2, R_f is selected from the group consisting of linear or branched perfluoroalkanediyl groups or perfluoroalkylidene
25 groups having from 2 to about 15 carbon atoms, perfluorocycloalkyl- or perfluorocycloalkylene-containing perfluoroalkanediyl or perfluoroalkylidene groups having from 6 to about 15 carbon atoms, and perfluorocycloalkanediyl groups or
30 perfluorocycloalkylidene groups having from 3 to about 12 carbon atoms; when x is 3, R_f is selected from the
















group consisting of linear or branched
perfluoroalkanetriyl groups having from 2 to about 15
carbon atoms, perfluorocycloalkyl- or
perfluorocycloalkylene-containing perfluoroalkanetriyl
5 groups having from 6 to about 15 carbon atoms, and
perfluorocycloalkanetriyl groups having from 3 to about
12 carbon atoms; each R_h is independently selected from
the group consisting of linear or branched alkyl groups
having from 1 to about 8 carbon atoms, cycloalkyl-
10 containing alkyl groups having from 4 to about 8 carbon
atoms, and cycloalkyl groups having from 3 to about 8
carbon atoms; wherein either or both of the groups R_f
and R_h can contain (optionally contain) one or more
catenary heteroatoms; and wherein the sum of the number
15 of carbon atoms in R_f and the number of carbon atoms in
 R_h is greater than or equal to 4. The
perfluorocycloalkyl and perfluorocycloalkylene groups
contained within the perfluoroalkyl,
perfluoroalkanediyl, perfluoroalkylidene and
20 perfluoroalkanetriyl groups can optionally (and
independently) be substituted with, e.g., one or more
perfluoroalkyl groups having from 1 to about 4 carbon
atoms.

Preferably, x is 1; R_f is as defined above; R_h
25 is an alkyl group having from 1 to about 6 carbon
atoms; R_f but not R_h can contain one or more catenary
heteroatoms; and the sum of the number of carbon atoms
in R_f and the number of carbon atoms in R_h is greater
than or equal to 4. Most preferably, x is 1; R_f is
30 selected from the group consisting of linear or
branched perfluoroalkyl groups having from 3 to about 6

carbon atoms, perfluorocycloalkyl-containing perfluoroalkyl or perfluoroalkylidene groups having from 5 to about 8 carbon atoms, and perfluorocycloalkyl groups having from 5 to about 6 carbon atoms; R_h is an alkyl group having from 1 to about 3 carbon atoms; R_f but not R_h can contain one or more catenary heteroatoms; and the sum of the number of carbon atoms in R_f and the number of carbon atoms in R_h is greater than or equal to 4. The perfluorocycloalkyl and perfluorocycloalkylene groups contained within the perfluoroalkyl, perfluoroalkanediyl, perfluoroalkylidene and perfluoroalkanetriyl groups can optionally (and independently) be substituted with, e.g., one or more perfluoromethyl groups. These compounds are preferred due to their ease of preparation and their performance characteristics.


Representative examples of alkoxy-substituted perfluorocompounds suitable for use in the processes of the invention include the following compounds:





and 1,1-dimethoxyperfluorocyclohexane, where cyclic structures having an interior "F" are perfluorinated.


















A novel subclass of the alkoxy-substituted perfluorocompounds is that which can be represented by the following general formula (II):



wherein R_f^1 and R_f^2 are both substituted or unsubstituted
5 perfluoroalkyl groups having from 1 to about 6 carbon
atoms or are both substituted or unsubstituted
perfluoroalkylene groups having from 2 to about 4
carbon atoms, the perfluoroalkylene groups being bonded
to one another to form a ring; y is an integer of 1 to
10 about 8; $C_y F_{2y}$ can be linear or branched; and R_h is
selected from the group consisting of linear or
branched alkyl groups having from 1 to about 8 carbon
atoms, cycloalkyl-containing alkyl groups having from 4
to about 8 carbon atoms, and cycloalkyl groups having
15 from 3 to about 8 carbon atoms; wherein the groups R_f^1 ,
 R_f^2 , and R_h can optionally (and independently) contain
one or more catenary heteroatoms.

Preferably, the perfluoroalkyl groups have
from 1 to about 3 carbon atoms, the perfluoroalkylene
20 groups have from 2 to about 3 carbon atoms; y is an
integer of 1 to about 3; R_h is selected from the group
consisting of linear or branched alkyl groups having
from 1 to about 6 carbon atoms; and R_f^1 and R_f^2 but not
 R_h can independently contain one or more catenary
25 heteroatoms. These compounds are preferred due to
their ease of preparation and their performance
characteristics.

Representative examples of novel compounds
according to Formula II above include the following
30 compounds:




A second novel subclass of the alkoxy-substituted perfluorocompounds is that which can be represented by the following general formula (III):



wherein R_f^3 is a substituted or unsubstituted perfluorocycloalkyl, perfluorocycloalkanediyl, or perfluorocycloalkanetriyl group having from 3 to about
10 12 carbon atoms; each R_h is independently selected from the group consisting of linear or branched alkyl groups having from 1 to about 8 carbon atoms, cycloalkyl-containing alkyl groups having from 4 to about 8 carbon atoms, and cycloalkyl groups having from 3 to about 8
15 carbon atoms; and x' is an integer of 1 to 3; wherein either or both of the groups R_f^3 and R_h can contain (optionally contain) one or more catenary heteroatoms.

Preferably, R_f^3 has from 5 to about 6 carbon atoms; each R_h is independently selected from the group
20 consisting of linear or branched alkyl groups having from 1 to about 6 carbon atoms; x' is an integer of 1 or 2; and R_f^3 but not R_h can contain one or more catenary heteroatoms. These compounds are preferred due to their ease of preparation and their performance
25 characteristics.

Representative examples of novel compounds according to Formula III above include the following compounds:



5

The alkoxy-substituted perfluorocompounds suitable for use in the process of the invention can be prepared by alkylation of perfluorinated alkoxides prepared by the reaction of the corresponding

10 perfluorinated acyl fluoride or perfluorinated ketone

with an anhydrous alkali metal fluoride (e.g.,
potassium fluoride or cesium fluoride) or anhydrous
silver fluoride in an anhydrous polar, aprotic solvent.
(See, e.g., the preparative methods described in French
5 Patent Publication No. 2,287,432 and German Patent
Publication No. 1,294,949, supra.) Alternatively, a
fluorinated tertiary alcohol can be allowed to react
with a base, e.g., potassium hydroxide or sodium
hydride, to produce a perfluorinated tertiary alkoxide
10 which can then be alkylated by reaction with alkylating
agent.

Suitable alkylating agents for use in the
preparation include dialkyl sulfates (e.g., dimethyl
sulfate), alkyl halides (e.g., methyl iodide), alkyl
15 p-toluenesulfonates (e.g., methyl p-toluenesulfonate),
alkyl perfluoroalkanesulfonates (e.g., methyl
perfluoromethanesulfonate), and the like. Suitable
polar, aprotic solvents include acyclic ethers such as
diethyl ether, ethylene glycol dimethyl ether, and
20 diethylene glycol dimethyl ether; carboxylic acid
esters such as methyl formate, ethyl formate, methyl
acetate, diethyl carbonate, propylene carbonate, and
ethylene carbonate; alkyl nitriles such as
acetonitrile; alkyl amides such as
25 N,N-dimethylformamide, N,N-diethylformamide, and
N-methylpyrrolidone; alkyl sulfoxides such as dimethyl
sulfoxide; alkyl sulfones such as dimethylsulfone,
tetramethylene sulfone, and other sulfolanes;
oxazolidones such as N-methyl-2-oxazolidone; and
30 mixtures thereof.

Perfluorinated acyl fluorides (for use in

preparing the alkoxy-substituted perfluorocompounds) can be prepared by electrochemical fluorination (ECF) of the corresponding hydrocarbon carboxylic acid (or a derivative thereof), using either anhydrous hydrogen fluoride (Simons ECF) or $KF \cdot 2HF$ (Phillips ECF) as the electrolyte. Perfluorinated acyl fluorides and perfluorinated ketones can also be prepared by dissociation of perfluorinated carboxylic acid esters (which can be prepared from the corresponding hydrocarbon or partially-fluorinated carboxylic acid esters by direct fluorination with fluorine gas). Dissociation can be achieved by contacting the perfluorinated ester with a source of fluoride ion under reacting conditions (see the method described in U.S. Patent No. 3,900,372 (Childs), the description of which is incorporated herein by reference) or by combining the ester with at least one initiating reagent selected from the group consisting of gaseous, non-hydroxylic nucleophiles; liquid, non-hydroxylic nucleophiles; and mixtures of at least one non-hydroxylic nucleophile (gaseous, liquid, or solid) and at least one solvent which is inert to acylating agents.

Initiating reagents which can be employed in the dissociation are those gaseous or liquid, non-hydroxylic nucleophiles and mixtures of gaseous, liquid, or solid, non-hydroxylic nucleophile(s) and solvent (hereinafter termed "solvent mixtures") which are capable of nucleophilic reaction with perfluorinated esters. The presence of small amounts of hydroxylic nucleophiles can be tolerated. Suitable

gaseous or liquid, non-hydroxylic nucleophiles include dialkylamines, trialkylamines, carboxamides, alkyl sulfoxides, amine oxides, oxazolidones, pyridines, and the like, and mixtures thereof. Suitable non-

5 hydroxylic nucleophiles for use in solvent mixtures include such gaseous or liquid, non-hydroxylic nucleophiles, as well as solid, non-hydroxylic nucleophiles, e.g., fluoride, cyanide, cyanate, iodide, chloride, bromide, acetate, mercaptide, alkoxide,

10 thiocyanate, azide, trimethylsilyl difluoride, bisulfite, and bifluoride anions, which can be utilized in the form of alkali metal, ammonium, alkyl-substituted ammonium (mono-, di-, tri-, or tetra-substituted), or quaternary phosphonium salts, and

15 mixtures thereof. Such salts are in general commercially available but, if desired, can be prepared by known methods, e.g., those described by M. C. Sneed and R. C. Brasted in Comprehensive Inorganic Chemistry, Volume Six (The Alkali Metals), pages 61-64, D. Van

20 Nostrand Company, Inc., New York (1957), and by H. Kobler et al. in *Justus Liebigs Ann. Chem.* **1978**, 1937. 1,4-diazabicyclo[2.2.2]octane and the like are also suitable solid nucleophiles.

The cleaning process of the invention can be

25 carried out by contacting a contaminated substrate with a cleaning composition comprising at least one of the above-described alkoxy-substituted perfluorocompounds. The perfluorocompounds can be utilized alone or in admixture with each other or with other commonly-used

30 cleaning solvents, e.g., alcohols, ethers, alkanes, alkenes, perfluorocarbons, perfluorinated tertiary

amines, perfluoroethers, cycloalkanes, esters, ketones, aromatics, siloxanes, hydrochlorocarbons, hydrochlorofluorocarbons, and hydrofluorocarbons.

Such co-solvents can be chosen to modify or enhance the solvency properties of a cleaning composition for a particular use and can be utilized in ratios (of co-solvent to perfluorocompound(s)) such that the resulting composition has no flash point. Preferably, the perfluorocompound(s) used in the composition have boiling points in the range of from about 25°C to about 200°C, more preferably from about 25°C to about 125°C.

To remove soils from fiber and textile substrates, the cleaning process of the invention can be carried out by contacting the fiber or textile with a cleaning composition comprising an alkoxy-substituted perfluoroalkane at ambient or elevated temperatures. The soiled textile can be agitated to promote the dissolving, dispersing or displacing of soil using any conventional agitation means including shaking, stirring and ultrasonic agitation. When the textile is sufficiently cleaned, the cleaning composition may be removed (e.g. by decantation), the textile optionally rinsed using an alkoxy-substituted perfluoroalkane or any conventional dry-cleaning solvent to ensure soil removal and prevent redeposition, and the textile can be dried, for example, by air-drying with or without added heat.

Optionally and preferably, the cleaning composition further comprises a surfactant. Suitable surfactants include those surfactants that are sufficiently soluble in the alkoxy-substituted

perfluoroalkane, and which promote soil removal by dissolving, dispersing or displacing the soil. One useful class of surfactants are those nonionic surfactants that have a hydrophilic-lipophilic balance (HLB) value of less than about 14. Examples include ethoxylated alcohols, ethoxylated alkylphenols, ethoxylated fatty acids, alkylaryl sulfonates, glycerol esters, ethoxylated fluoroalcohols, and fluorinated sulfonamides. Mixtures of surfactants having complementary properties may be used in which one surfactant is added to the cleaning composition to promote oily soil removal and another added to promote water-soluble soil removal.

The surfactant, if used, can be added in an amount sufficient to promote soil removal. Typically, surfactant is added in amounts from about 0.1 to 5.0 wt.%, preferably in amounts from about 0.2 to 2.0 wt.% of the cleaning composition.

The cleaning composition can be used in either the gaseous or the liquid state (or both), and any of the known techniques for "contacting" a substrate can be utilized. For example, a liquid cleaning composition can be sprayed or brushed onto the substrate, a gaseous cleaning composition can be blown across the substrate, or the substrate can be immersed in either a gaseous or a liquid composition. Elevated temperatures, ultrasonic energy, and/or agitation can be used to facilitate the cleaning. Various different solvent cleaning techniques are described by B. N. Ellis in Cleaning and Contamination of Electronics

Components and Assemblies, Electrochemical Publications Limited, Ayr, Scotland, pages 182-94 (1986).

Both organic and inorganic substrates can be cleaned by the process of the invention.

5 Representative examples of the substrates include metals; ceramics; glass; polycarbonate; polystyrene; acrylonitrile-butadiene-styrene copolymer; synthetic non-woven materials; natural fibers (and fabrics derived therefrom) such as cotton, silk, fur, suede,
10 leather, linen, and wool; synthetic fibers (and fabrics) such as polyester, rayon, acrylics, nylon, and blends thereof; fabrics comprising a blend of natural and synthetic fibers; and composites of the foregoing materials. The process is especially useful in the
15 precision cleaning of electronic components (e.g., circuit boards), optical or magnetic media, and medical devices.

The cleaning process of the invention can be used to dissolve or remove most contaminants from the
20 surface of a substrate. For example, materials such as light hydrocarbon contaminants; higher molecular weight hydrocarbon contaminants such as mineral oils and greases; fluorocarbon contaminants such as perfluoropolyethers, bromotrifluoroethylene oligomers
25 (gyroscope fluids), and chlorotrifluoroethylene oligomers (hydraulic fluids, lubricants); silicone oils and greases; solder fluxes; particulates; and other contaminants encountered in precision, electronic, metal, and medical device cleaning can be removed.
30 The process is particularly useful for the removal of hydrocarbon contaminants (especially, light hydrocarbon

oils), fluorocarbon contaminants, particulates, and water (as described in the next paragraph).

To displace or remove water from substrate surfaces, the cleaning process of the invention can be carried out as described in U.S. Patent No. 5,125,978 (Flynn et al.) by contacting the surface of an article with a liquid cleaning composition which preferably contains a non-ionic fluoroaliphatic surface active agent. The wet article is immersed in the liquid composition and agitated therein, the displaced water is separated from the liquid composition, and the resulting water-free article is removed from the liquid composition. Further description of the process and the articles which can be treated are found in said U.S. Patent No. 5,125,978, which description is incorporated herein by reference. The process can also be carried out as described in U.S. Patent No. 3,903,012 (Brandreth), the description of which is also incorporated herein.

This invention also provides a cleaning composition comprising (a) a major amount (preferably, at least about 60 percent of the composition by weight) of at least one mono-, di-, or trialkoxy-substituted perfluoroalkane, perfluorocycloalkane, perfluorocycloalkyl-containing perfluoroalkane, or perfluorocycloalkylene-containing perfluoroalkane compound, the compound optionally containing additional catenary heteroatoms; and (b) a minor amount of at least one co-solvent selected from the group consisting of alcohols, ethers, alkanes, alkenes, perfluorocarbons, perfluorinated tertiary amines,

perfluoroethers, cycloalkanes, esters, ketones, aromatics, siloxanes, hydrochlorocarbons, hydrochlorofluorocarbons, and hydrofluorocarbons.

Preferably, the co-solvent is selected from the group
5 consisting of alcohols, alkanes, alkenes, cycloalkanes, esters, aromatics, hydrochlorocarbons, and hydrofluorocarbons.

Representative examples of co-solvents which can be used in the cleaning composition include
10 methanol, ethanol, isopropanol, t-butyl alcohol, methyl t-butyl ether, methyl t-amyl ether, 1,2-dimethoxyethane, cyclohexane, 2,2,4-trimethylpentane, n-decane, terpenes (e.g., α -pinene, camphene, and limonene), trans-1,2-dichloroethylene,
15 methylcyclopentane, decalin, methyl decanoate, t-butyl acetate, ethyl acetate, diethyl phthalate, 2-butanone, methyl isobutyl ketone, naphthalene, toluene, p-chlorobenzotrifluoride, trifluorotoluene, hexamethyl disiloxane, octamethyl trisiloxane, perfluorohexane,
20 perfluoroheptane, perfluorooctane, perfluorotributylamine, perfluoro-N-methyl morpholine, perfluoro-2-butyl oxacyclopentane, methylene chloride, chlorocyclohexane, 1-chlorobutane, 1,1-dichloro-1-fluoroethane, 1,1,1-trifluoro-2,2-dichloroethane,
25 1,1,1,2,2-pentafluoro-3,3-dichloropropane, 1,1,2,2,3-pentafluoro-1,3-dichloropropane, 2,3-dihydroperfluoropentane, 1,1,1,2,2,4-hexafluorobutane, 1-trifluoromethyl-1,2,2-trifluorocyclobutane, 3-methyl-1,1,2,2-tetrafluorocyclobutane, and 1-
30 hydropentadecafluoroheptane.

The above-described alkoxy-substituted perfluorocompounds can be useful not only in cleaning but also in coating deposition, where the perfluorocompound functions as a carrier for a coating material to enable deposition of the material on the surface of a substrate. The invention thus also provides a coating composition and a process for depositing a coating on a substrate surface using the composition. The process comprises the step of applying to at least a portion of at least one surface of a substrate a coating of a liquid coating composition comprising (a) a solvent composition comprising at least one mono-, di-, or trialkoxy-substituted perfluoroalkane, perfluorocycloalkane, perfluorocycloalkyl-containing perfluoroalkane, or perfluorocycloalkylene-containing perfluoroalkane compound, the compound optionally containing additional catenary heteroatoms; and (b) at least one coating material which is soluble or dispersible in the solvent composition. The solvent composition can further comprise one or more co-dispersants or co-solvents (as defined supra, preferably those having boiling points below about 125°C) and/or one or more additives (e.g., surfactants, coloring agents, stabilizers, anti-oxidants, flame retardants, and the like). Preferably, the process further comprises the step of removing the solvent composition from the coating by, e.g., allowing evaporation (which can be aided by the application of, e.g., heat or vacuum).

Coating materials which can be deposited by the process include pigments, lubricants, stabilizers,

adhesives, anti-oxidants, dyes, polymers, pharmaceuticals, release agents, inorganic oxides, and the like, and combinations thereof. Preferred materials include perfluoropolyether, hydrocarbon, and
5 silicone lubricants; amorphous copolymers of tetrafluoroethylene; polytetrafluoroethylene; and combinations thereof. Representative examples of materials suitable for use in the process include titanium dioxide, iron oxides, magnesium oxide,
10 perfluoropolyethers, polysiloxanes, stearic acid, acrylic adhesives, polytetrafluoroethylene, amorphous copolymers of tetrafluoroethylene, and combinations thereof. Any of the substrates described above (for cleaning applications) can be coated via the process of
15 the invention. The process can be particularly useful for coating magnetic hard disks or electrical connectors with perfluoropolyether lubricants or medical devices with silicone lubricants.

To form a coating composition, the components
20 of the composition (i.e., the alkoxy-substituted perfluorocompound(s), the coating material(s), and any co-dispersant(s) or co-solvent(s) utilized) can be combined by any conventional mixing technique used for dissolving, dispersing, or emulsifying coating
25 materials, e.g., by mechanical agitation, ultrasonic agitation, manual agitation, and the like. The solvent composition and the coating material(s) can be combined in any ratio depending upon the desired thickness of the coating, but the coating material(s) preferably
30 constitute from about 0.1 to about 10 weight percent of the coating composition for most coating applications.

The deposition process of the invention can be carried out by applying the coating composition to a substrate by any conventional technique. For example, the composition can be brushed or sprayed (e.g., as an aerosol) onto the substrate, or the substrate can be spin-coated. Preferably, the substrate is coated by immersion in the composition. Immersion can be carried out at any suitable temperature and can be maintained for any convenient length of time. If the substrate is a tubing, such as a catheter, and it is desired to ensure that the composition coats the lumen wall, it may be advantageous to draw the composition into the lumen by the application of reduced pressure.

After a coating is applied to a substrate, the solvent composition can be removed from the coating by evaporation. If desired, the rate of evaporation can be accelerated by application of reduced pressure or mild heat. The coating can be of any convenient thickness, and, in practice, the thickness will be determined by such factors as the viscosity of the coating material, the temperature at which the coating is applied, and the rate of withdrawal (if immersion is utilized).

Objects and advantages of this invention are further illustrated by the following examples, but the particular materials and amounts thereof recited in these examples, as well as other conditions and details, should not be construed to unduly limit this invention.

30

Examples

The environmental impact of the alkoxy-substituted perfluorocompounds used in the processes and compositions of the invention was assessed by
5 determination of the atmospheric lifetime and the global warming potential (GWP) of certain compounds, as described below:

Atmospheric Lifetime

10 The atmospheric lifetime (t_{sample}) of various sample compounds was calculated by the technique described in Y. Tang, Atmospheric Fate of Various Fluorocarbons, M.S. Thesis, Massachusetts Institute of Technology (1993). According to this technique, an ultraviolet
15 (UV) gas cell was charged with a sample compound, a reference compound (either CH_4 or CH_3Cl), ozone, and water vapor. Hydroxyl radicals were then generated by photolytic decomposition of the ozone in the presence of the water vapor and an inert buffer gas, i.e.,
20 helium. As the sample compounds and reference compounds reacted with the hydroxyl radicals in the gas phase, their concentrations were measured by Fourier transform infrared spectroscopy (FTIR). The rate constant for reaction of the sample compound (k_{sample})
25 with hydroxyl radical was measured relative to the rate constant for a reference compound (k_{ref}), and the atmospheric lifetime was then calculated using the following formula (where t_{CH_4} and k_{CH_4} are known values):

$$\tau_{sample} = \frac{\tau_{CH_4}}{\left(\frac{k_{sample}}{k_{ref}}\right)\left(\frac{k_{ref}}{k_{CH_4}}\right)}$$

5

The rate constant for each sample compound was measured (using CH₄ as the reference compound and again using CH₃Cl) at 298K, and the atmospheric lifetime values were calculated and then averaged. The results are shown in Table A under the heading "Atmospheric Lifetime." For comparative purposes, the atmospheric lifetime for several hydrofluorocarbons is also shown in Table A.

Atmospheric lifetime was also estimated from a correlation developed between the highest occupied molecular orbital (HOMO) energy and the known atmospheric lifetimes of hydrofluorocarbons and hydrofluorocarbon ethers, in a manner similar to that described by Cooper et al. in Atmos. Environ. 26A, 7, 1331 (1992). The correlation differed from that found in Cooper et al. in the following respects: the correlation was developed using a larger data set; lifetimes for the correlations were determined by relative hydroxyl reactivity of the sample to CH₃CCl₃ at 277K, as described by Zhang et al. in J. Phys. Chem. 98(16), 4312 (1994); HOMO energy was calculated using MOPAC/PM3, a semi-empirical molecular orbital package; and the number of hydrogen atoms present in the sample was included in the correlation. The results are reported in Table A under the heading "Estimated Atmospheric Lifetime."

Global Warming Potential

Global warming potential (GWP) was determined for the various sample compounds using the above-described calculated values for atmospheric lifetime and experimentally determined infrared absorbance data integrated over the spectral region of interest, typically 500 to 2500 cm^{-1} . The calculations were based on the definition of GWP set forth by the Intergovernmental Panel in Climate Change in Climate Change: The IPCC Scientific Assessment, Cambridge University Press (1990). According to the Panel, GWP is the integrated potential warming due to the release of 1 kilogram of sample compound relative to the warming due to 1 kilogram of CO_2 over a specified integration time horizon (ITH) using the following equation:

$$GWP_{\text{sample}} = \frac{\int_0^{\text{ITH}} \Delta T_i C_{\text{sample}} e^{-t/\tau_i} dt}{\int_0^{\text{ITH}} \Delta T_{\text{CO}_2} C_{\text{CO}_2} dt}$$

where ΔT is the calculated change in temperature at the earth's surface due to the presence of a particular compound in the atmosphere [calculated using a spreadsheet model (using parameters described by Fisher et al. in Nature 344, 513 (1990)) derived from Atmospheric and Environmental Research, Inc.'s more complete one-dimensional radiative-convective model (described by Wang et al. in J. Atmos. Sci. 38, 1167 (1981) and J. Geophys. Res. 90, 12971 (1985))], C is the

atmospheric concentration of the compound, t is the atmospheric lifetime of the compound (the calculated value described above), and x designates the compound of interest. Upon integration, the formula is as

5 follows:

where $A_1 = 0.30036$, $A_2 = 0.34278$, $A_3 = 0.35686$, $\tau_1 = 6.993$, $\tau_2 = 71.108$, and $\tau_3 = 815.73$ in the Siegenthaler

$$GWP_{\text{sample}} = \frac{\Delta T_x C_o \tau_x [1 - e^{-ITH/\tau_x}]}{\Delta T_{CO_2} (1.3 \times 10^{-10}) [A_1 \tau_1 (1 - e^{-ITH/\tau_1}) + A_2 \tau_2 (1 - e^{-ITH/\tau_2}) + A_3 \tau_3 (1 - e^{-ITH/\tau_3})]}$$

(1983) coupled ocean-atmosphere CO_2 model. The results of the calculations are shown in Table A below.

10

Table A

Compound	Estimated Atmospheric Lifetime (years)	Atmospheric Lifetime (years)	Global Warming Potential (100 year ITH)
CF_3-CH_3	62.2		
CF_3-O-CH_3	1.6		
$C_2F_5-CH_3$	12.6		
$C_2F_5-O-CH_3$	1.6		
$C_3F_7-CH_3$	9.6		
$C_3F_7-O-CH_3$	1.9		
$C_4F_9-CH_3$	7.0		
$C_4F_9-O-CH_3$	1.9	5.5	330
$C_4F_9-C_2H_5$	2.0		
$C_4F_9-O-C_2H_5$	0.5	1.2	70
$C_5F_{11}OCH_3$	4.3		
$CF_3CF(OCH_3)CF(CF_3)_2$	4-5		
$C_5F_{11}OC_2H_5$	~1		
$C-C_6F_{11}-CH_3$	13.7		

Compound	Estimated Atmospheric Lifetime (years)	Atmospheric Lifetime (years)	Global Warming Potential (100 year ITH)
$\text{C}-\text{C}_6\text{F}_{11}-\text{O}-\text{CH}_3$	1.8	3.8	170
$\text{C}_2\text{F}_5\text{CF}(\text{OCH}_3)\text{CF}(\text{CF}_3)_2$	4-5		
$\text{CF}_3\text{CFHCFHCF}_2\text{CF}_3$	23*		1000

* A. M. Schmoltner et al., J. Phys. Chem. 97, 8976
(1993)

5 As can be seen in Table A, each of the various
alkoxy-substituted perfluorocompounds unexpectedly has
a lower atmospheric lifetime than the corresponding
hydrofluorocarbon, i.e., the hydrofluorocarbon having
the same carbon number. The alkoxy-substituted
10 perfluorocompounds are thus more environmentally
acceptable than the hydrofluorocarbons (which have
previously been proposed as chlorofluorocarbon
replacements).

15 The chemical stability of the alkoxy-substituted
perfluorocompounds used in the processes and
compositions of the invention was also evaluated to
determine their suitability for use in cleaning and
coating applications. In these tests, a compound was
contacted with a chemical agent such as aqueous sodium
20 acetate, aqueous KOH, concentrated sulfuric acid, or
potassium permanganate in acetone to determine the
stability of the compound to base, acid, or oxidant, as
described below:

Stability in the Presence of Base

To assess hydrolytic stability, a ten gram sample of alkoxy-substituted perfluorocompound was combined with 10 g of 0.1M NaOAc and sealed in a 2.54 cm (internal diameter) by 9.84 cm Monel™ 400 alloy (66% nickel, 31.5% copper, and 1.2% iron and several minor components) tube (available from Paar Instrument Co. of Moline, Illinois as Part Number 4713cm). The tube was heated at 110°C in a forced air convection oven for 16 hours. After cooling to room temperature, a 1 mL sample of the tube contents was diluted with 1 mL of total ionic strength adjustment buffer (TISAB, available from Orion Research, Inc., a mixture of 1,2-cyclohexylene dinitrilotetraacetic acid, deionized water, sodium acetate, sodium chloride, and acetic acid). The concentration of fluoride ion (resulting from any reaction of the perfluorocompound with the aqueous NaOAc) was measured using an Orion Model 720A Coulombmeter with a F⁻ specific electrode which had been previously calibrated using 0.5 and 500 ppm F⁻ solutions. Based on the measured fluoride ion concentration, the rate at which HF had been generated by reaction of the aqueous NaOAc with the perfluorocompound was calculated. The results are shown below in Table B and indicate that the alkoxy-substituted perfluorocompounds are much more stable to base than is the comparative compound.

Table B

	$C_4F_9OCH_3$	$C_4F_9OC_2H_5$	$c-C_6F_{11}OCH_3$	$CF_3CFHCFHCF_2CF_3$
HF Generation Rate ($\mu\text{g/g/hr}$)	0.67	0.22	0.33	42.9

To assess hydrolytic stability under more severely basic conditions, $C_4F_9OCH_3$ (125 g of 99.8% purity, 0.5 mole) was combined with potassium hydroxide (29.4 g, 0.45 mole, dissolved in 26.1 g water) in a 250 mL flask equipped with an overhead stirrer, a condenser, and a thermometer, and the resulting solution was refluxed at 58°C for 19 hours. Water (50 mL) was added to the solution after refluxing, and the resulting product was distilled. The lower fluorochemical phase of the resulting distillate was separated from the upper phase and was washed with water (100 mL) to yield 121.3 g of recovered $C_4F_9OCH_3$, which was identical in purity and composition to the starting material (as shown by gas chromatography). The aqueous base solution remaining in the reaction flask was titrated with standard 1.0 N HCl to reveal that none of the KOH originally charged had been consumed, indicating that the perfluorocompound was stable in the presence of the base.

Stability in the Presence of Acid

To assess hydrolytic stability under acidic conditions, $C_4F_9OCH_3$ (15 g, 0.06 mole) was combined with sulfuric acid (10 g of 96% by weight, 0.097 mole) in a 50 mL flask containing a stir bar and fitted with a

reflux condenser. The resulting mixture was stirred for 16 hours at room temperature, and then the resulting upper fluorochemical phase was separated from the resulting lower sulfuric acid phase. Gas-liquid chromatographic (GLC) analysis of the fluorochemical phase revealed the presence of only the starting perfluorocompound and no detectable amount of $C_3F_7CO_2CH_3$, the expected product of hydrolysis. This result (indicating that the perfluorocompound was stable in the presence of the acid) was surprising in view of the discussion by England in J.Org. Chem. 49, 4007 (1984), which states that "[f]luorine atoms attached to carbon which also bears an alkyl ether group are known to be labile to electrophilic reagents. They are readily hydrolyzed in concentrated sulfuric acid, thus providing a route to some esters of fluoroacids."

Stability in the Presence of Oxidant

To assess oxidative stability, potassium permanganate (20 g, 0.126 mole) was dissolved in acetone, and $C_4F_9OCH_3$ (500 g of 99.9% purity, 2.0 mole) was added to the resulting solution. The solution was refluxed for four hours, with no indication that the permanganate had been consumed (as evidenced by the absence of brown MnO_2). The refluxed solution was then distilled into a 500 mL Barrett trap filled with water. The lower fluorochemical phase of the resulting mixture was separated from the upper phase, was washed with four 1.5 L aliquots of water, and was dried by passage through a column of silica gel to yield 471 g of resulting product. Gas chromatographic analysis of the

product revealed no evidence of degradation of the starting perfluorocompound, indicating that the compound was stable in the presence of the oxidant.

5 **Flash Point Testing**

The alkoxy-substituted perfluorocompounds $C_4F_9OCH_3$, $C_4F_9OC_2H_5$, and $c-C_6F_{11}OCH_3$ were tested for flash point by the standard method defined by ASTM D3278-89. Each compound was determined to have no flash point.

10

Examples 1-7 describe the preparation of novel alkoxy-substituted perfluorocompounds of the invention.

Example 1

15 **Preparation of $c-C_6F_{11}CF_2OC_2H_5$**

A one liter jacketed round bottom flask was equipped with a reflux condenser, an overhead stirrer, and an addition funnel. The flask was charged with anhydrous dimethyl formamide (300 g) and diethyl sulfate (239 g, 1.55 mole) under a flow of dry nitrogen gas. The resulting stirred solution was cooled to $-20^\circ C$, and spray-dried potassium fluoride (Aldrich Chemical, which was further dried at $120^\circ C$, 67.5 g, 1.16 mole) was added. A mixture of

20 perfluorocyclohexane carbonyl fluoride and isomers of perfluoro methylcyclopentane carbonyl fluoride (approximately 80% purity, 318 g, 0.77 mole) was then added to the resulting mixture over a period of 45 minutes. (Hereinafter, $c-C_6F_{11}$ - refers to a mixture

25 of the perfluorinated cyclohexyl and methyl cyclopentyl isomers.) The mixture was held at $-20^\circ C$ for two hours

30

and then allowed to come to ambient temperature while stirring overnight. The mixture was transferred to a two liter round bottom flask and was heated to 50°C for one hour. One liter of water was added and the
5 resulting mixture distilled. The lower fluorochemical phase of the resulting distillate was then separated from the upper phase and was washed once with water to afford 236 g of 61.9 % purity $c\text{-C}_6\text{F}_{11}\text{CF}_2\text{OC}_2\text{H}_5$. The product was distilled to a purity of 99% (b.=128-
10 134°C). The product identity was confirmed by gas chromatography/ mass spectrometry (GCMS) and by ^1H and ^{19}F nuclear magnetic resonance spectroscopy (NMR).

Example 2

15 Preparation of $c\text{-C}_6\text{F}_{11}\text{CF}_2\text{OCH}_3$

A 500 mL round bottom flask was equipped with an overhead stirrer, a condenser, and an addition funnel, and was then charged with spray-dried potassium fluoride (Aldrich, which was further dried at 120°C,
20 39.8 g, 0.68 mole) and anhydrous dimethyl formamide (250 g). $c\text{-C}_6\text{F}_{11}\text{COF}$ (150 g of 70% purity, 0.32 mole) was added slowly to the resulting mixture at room temperature. An ice bath was then placed around the flask, and dimethyl sulfate (74.8 g, 0.59 mole) was
25 added dropwise. The resulting mixture was held in the ice bath for five hours, followed by warming to ambient temperature with stirring overnight. Water (100 mL) was then added to the mixture, and the resulting product was distilled. The lower fluorochemical phase of the
30 resulting distillate was separated from the upper aqueous phase to yield 143 g of $c\text{-C}_6\text{F}_{11}\text{CF}_2\text{OCH}_3$ of 63%

purity. The products of several reactions were combined and distilled (b.=110-120°C). The product identity was confirmed by GCMS and by ^1H and ^{19}F NMR.

5 Example 3

Preparation of 4-CF₃-c-C₆F₁₀CF₂OCH₃


A one liter round bottom flask was equipped with an overhead stirrer, a condenser, and an addition funnel and was then charged with spray-dried potassium
10 fluoride (Aldrich, which was further dried at 120°C, 15.4 g, 0.26 mole), anhydrous cesium fluoride (6.5 g, 0.043 mole), and anhydrous dimethyl formamide (250 g). A mixture of perfluoro-4-methylcyclohexane carbonyl fluoride and perfluorodimethyl cyclopentane carbonyl
15 fluorides (100 g of 72% purity, 0.189 mole) was then added to the resulting mixture, and the mixture was stirred at ambient temperature for four hours. Dimethyl sulfate (33.3 g, 0.264 mole) was then added to the stirred mixture, and the mixture was further
20 stirred for 72 hours followed by addition of water (500 mL).

The mixture was worked up essentially as described in Example 1 to yield 67 g of a mixture of several components, which was subsequently distilled to
25 give 26.5 g of 4-CF₃-c-C₆F₁₀CF₂OCH₃ (b.=118-137°C) of 88% purity. The product identity was confirmed by GCMS and by ^1H and ^{19}F NMR, which showed the product to be about 60% of the trans-1,4 isomer and 15% of the cis-1,4 isomer. The product also contained several other
30 isomers of CF₃-c-C₆F₁₀CF₂OCH₃, resulting from isomers of

the perfluoromethylcyclohexane carbonyl fluoride which were present in the starting material.

Example 4


5 Preparation of



The title compound was prepared essentially as in Example 3 using anhydrous potassium fluoride (27 g, 0.46 mole), anhydrous dimethyl formamide (250 g),
 10 perfluoro-3- piperidinopropionyl fluoride (322 g of 40.4% purity, 0.32 mole), and dimethyl sulfate (52 g, 0.41 mole). 275 g of a product mixture of 38% purity was obtained, which was fractionally distilled to give a main fraction of the desired compound (b.=137-139°C,
 15 91% purity). The product identity was confirmed by infrared spectroscopy (IR), GCMS, and ^1H and ^{19}F NMR.

Example 5

Preparation of




The title compound was prepared essentially as in Example 3 using anhydrous potassium fluoride (42 g, 0.72 mole), anhydrous dimethyl formamide (300 g),
 perfluoro-2-piperidinoacetyl fluoride (354 g of 47.2%
 25 purity, 0.46 mole), and diethyl sulfate (94 g, 0.61 mole). 349 g of a product mixture of 39% purity was obtained, which was fractionally distilled to give a main fraction of the desired compound (b.=135-137°C).

The product identity was confirmed by IR, GCMS, and ^1H and ^{19}F NMR.

Example 6

5 Preparation of



The title compound was prepared essentially as in Example 3 using anhydrous potassium fluoride (17.7 g, 0.30 mole), anhydrous dimethyl formamide (300 g), perfluoro-3-morpholinopropionyl fluoride (890 g of 8.6% purity, 0.2 mole), and dimethyl sulfate (37 g, 0.29 mole). 88 g of a product mixture of 57% purity was obtained, which was fractionally distilled to give a main fraction of the desired compound (b.p.=129°C, 90% purity). The product identity was confirmed by IR, GCMS, and ^1H and ^{19}F NMR.

Example 7

Preparation of $\text{CH}_3\text{OCF}_2\text{-c-C}_6\text{F}_{10}\text{CF}_2\text{OCH}_3$

The title compound was prepared essentially as in Example 3 using anhydrous potassium fluoride (6.62 g, 0.011 mole), anhydrous dimethyl formamide (200 g), FCO-c-C₆F₁₀COF (253 g of approximately 26% purity, 0.185 mole; the remainder of the material comprised a mixture of mono-functional, non-functional, and isomeric compounds), and dimethyl sulfate (14.4 g, 0.011 mole). 21 g of solid $\text{CH}_3\text{OCF}_2\text{-c-C}_6\text{F}_{10}\text{CF}_2\text{OCH}_3$ was obtained (product identity confirmed by IR and ^1H and ^{19}F NMR).

Examples 8-28 describe the use of alkoxy-substituted perfluorocompounds in various different cleaning applications according to the cleaning process of the invention.

A number of different alkoxy-substituted perfluorocompounds were prepared for use in cleaning, as described below:

10

Preparation of $C_4F_9OC_2H_5$

A 20 gallon Hastalloy C reactor, equipped with a stirrer and a cooling system, was charged with spray-dried potassium fluoride (7.0 kg, 120.3 mole). The reactor was sealed, and the pressure inside the reactor was reduced to less than 100 torr. Anhydrous dimethyl formamide (22.5 kg) was then added to the reactor, and the reactor was cooled to below 0°C with constant agitation. Heptafluorobutyryl fluoride (22.5 kg of 58% purity, 60.6 mole) was added to the reactor contents. When the temperature of the reactor reached -20°C, diethyl sulfate (18.6 kg, 120.8 mole) was added to the reactor over a period of approximately two hours. The resulting mixture was then held for 16 hours with continued agitation, was raised to 50°C for an additional four hours to facilitate complete reaction, and was cooled to 20°C. Then, volatile material (primarily perfluorooxacyclopentane present in the starting heptafluorobutyryl fluoride) was vented from the reactor over a three-hour period. The reactor was

15

20

25

30

then resealed, and water (6.0 kg) was added slowly to the reactor. After the exothermic reaction of the water with unreacted perfluorobutyryl fluoride subsided, the reactor was cooled to 25°C, and the reactor contents were stirred for 30 minutes. The reactor pressure was carefully vented, and the lower organic phase of the resulting product was removed to afford 17.3 kg of material which was 73% $C_4F_9OC_2H_5$ (b.p.=75°C). The product identity was confirmed by GCMS and by 1H and ^{19}F NMR.

Preparation of $C_4F_9OCH_3$

The reaction was carried out in the same equipment and in a similar manner to the procedure of Example 7 above, but using the following materials: spray-dried potassium fluoride (6 kg, 103.1 mole), anhydrous dimethyl formamide (25.1 kg), perfluorobutyryl fluoride (58% purity, 25.1 kg, 67.3 mole), and dimethyl sulfate (12.0 kg, 95.1 mole). 22.6 kg of product was obtained, which was 63.2% $C_4F_9OCH_3$ (b.=58-60°C). The product identity was confirmed by GCMS and by 1H and ^{19}F NMR.

Preparation of c- $C_6F_{11}OCH_3$

A 500 ml, 3-necked round bottom flask equipped with an overhead stirrer, an addition funnel, and a condenser was charged with anhydrous cesium fluoride (27.4 g, 0.18 mole), anhydrous diethylene glycol dimethyl ether (258 g, hereinafter diglyme), and dimethyl sulfate (22.7 g, 0.18 mole). Perfluorocyclohexanone (50g, 0.18 mole) was then added

dropwise to the resulting stirred mixture, and stirring was continued for 18 hours after the addition. Water (approximately 200 ml) was added to the resulting mixture, and the lower fluorochemical phase of the mixture was separated from the upper phase and washed once with saturated aqueous sodium chloride solution. Since the fluorochemical phase still contained about 12% diglyme, water was added to it, and the resulting product was azeotropically distilled to yield 32.8 g of c-C₆F₁₁OCH₃ (b.p.=100°C), which was free of diglyme. The product identity was confirmed by IR, GCMS, and ¹H and ¹⁹F NMR.

Preparation of (CF₃)₂CFCF₂OCH₃

The title compound was prepared essentially as in Example 1 using anhydrous potassium fluoride (31.9 g, 0.55 mole), anhydrous dimethyl formamide (186 g), perfluoroisobutryl fluoride (108 g of 99% purity, 0.5 mole), and dimethyl sulfate (81.9 g, 0.65 mole). The resulting mixture was held at -20°C for 16 hours, was warmed to 40°C for 3.5 hours, and was then distilled to yield 109 g of the title compound (83.6% purity by GLC; also containing 11.6% (CF₃)₂CFCOF). The reaction mixtures from several runs were combined and distilled (b.=60-61°C).

Preparation of (CF₃)₂CFCF₂OC₂H₅

The title compound was prepared essentially as in Example 1 using anhydrous potassium fluoride (31.9 g, 0.55 mole), anhydrous dimethyl formamide (184 g), perfluoroisobutryl fluoride (112.3 g of 77%

purity, 0.4 mole), and diethyl sulfate (100.1 g, 0.65 mole). The resulting mixture was worked up essentially as in Example 3 to yield 80 g of the title compound. The product identity was confirmed by IR, GCMS, and ^1H and ^{19}F NMR.

Preparation of $\text{C}_8\text{F}_{17}\text{OCH}_3$

The title compound was prepared essentially as in Example 3 using anhydrous potassium fluoride (6.62 g, 0.011 mole), anhydrous dimethyl formamide (800 g), $\text{C}_7\text{F}_{15}\text{COF}$ (456.7 g, 1.09 mole), and dimethyl sulfate (14.4 g, 0.011 mole). The resulting mixture was worked up essentially as in Example 3 to give 444 g of the title compound (99.7% purity, b.=142-144°C). The product identity was confirmed by IR, GCMS, and ^1H and ^{19}F NMR.

Preparation of $\text{C}_2\text{F}_5\text{CF}(\text{OCH}_3)\text{CF}(\text{CF}_3)_2$

The title compound was prepared essentially as in Example 3 using anhydrous potassium fluoride (7.2 g, 0.123 mol), anhydrous diethylene glycol dimethyl ether (diglyme, 60 g), methyltrialkyl($\text{C}_8\text{-C}_{10}$) ammonium chloride (Adogen™ 464, available from Aldrich Chemical Company, 1.8 g), $\text{C}_2\text{F}_5\text{COCF}(\text{CF}_3)_2$ (30 g, 0.095 mol, prepared by the reaction of pentafluoropropionyl fluoride with KF and hexafluoropropene), and dimethyl sulfate (15.5 g, 0.123 mol). The reaction mixture was stirred at room temperature for 72 hours. Approximately 100 mL of 10% aqueous potassium hydroxide was then added to the reaction mixture, and the resulting product was

azeotropically distilled from the mixture. The lower phase of the resulting distillate was separated from the upper phase, was washed with water, and was distilled to give 26.7 g of product ether (boiling range 90-92°C; >99% purity by gas-liquid chromatography (GLC)). The product identity was confirmed by GCMS and ¹H and ¹⁹F NMR.

Preparation of C₃F₇OCH₃

10 A jacketed one liter round bottom flask was equipped with an overhead stirrer, a solid carbon dioxide/acetone condenser, and an addition funnel. The flask was charged with spray-dried potassium fluoride (85 g, 1.46 mol) and anhydrous diethylene glycol dimethyl ether (375 g) and was then cooled to about -20°C using a recirculating refrigeration system. C₂F₅COF (196 g, 1.18 mol) was added to the flask over a period of about one hour. The flask was then warmed to about 24°C, and dimethyl sulfate (184.3 g, 1.46 mol) was then added dropwise via the addition funnel over a 45 minute period. The resulting mixture was then stirred at room temperature overnight. Water (a total of 318 mL) was then added dropwise to the mixture. The mixture was transferred to a one liter round bottom flask, and the resulting product ether was azeotropically distilled. The lower product phase of the resulting distillate was separated from the upper aqueous phase, was washed once with cold water, and was subsequently distilled to give 180 g of product (b.p. 36°C; >99.9% purity by GLC). The product identity was confirmed by GCMS and by ¹H and ¹⁹F NMR.

Preparation of $\text{CF}_3\text{CF}(\text{OCH}_3)\text{CF}(\text{CF}_3)_2$

The title compound was prepared essentially as in Example 3 using anhydrous potassium fluoride (12.8 g, 0.22 mol), anhydrous diethylene glycol dimethyl ether (diglyme, 106 g), methyltrialkyl($\text{C}_8\text{-C}_{10}$)ammonium chloride (Adogen™ 464, available from Aldrich Chemical Company, 4 g), $\text{CF}_3\text{COCF}(\text{CF}_3)_2$ (53.2 g, 0.20 mol, prepared essentially by the procedure of Smith et al., J. Am. Chem. Soc., 84, 4285 (1962)), and dimethyl sulfate (33.9 g, 0.72 mol). Aqueous potassium hydroxide was added to the reaction mixture (approximately 25 g of 50% solution), followed by water (200 mL). The resulting crude product was azeotropically distilled from the reaction mixture. The lower phase of the resulting distillate was separated from the upper phase, was washed with water, was dried over anhydrous sodium sulfate, and was distilled (b.p. 82-83°C; yield of 45 g). The product identity was confirmed by GCMS and by FTIR.

Preparation of $\text{C}_5\text{F}_{11}\text{OCH}_3$

The title compound was prepared essentially as in Example 3 using anhydrous potassium fluoride (32 g, 0.55 mol), anhydrous diethylene glycol dimethyl ether (diglyme, 375 g), methyltrialkyl($\text{C}_8\text{-C}_{10}$)ammonium chloride (Adogen™ 464, available from Aldrich Chemical Company, 12.5 g), $\text{C}_4\text{F}_9\text{COF}$ (218 g of 60.7% purity, 0.5 mol), and dimethyl sulfate (69.3 g, 0.55 mol). The reaction mixture was stirred at room temperature overnight. Approximately 100 mL of 10% aqueous

potassium hydroxide was then added to the mixture, and the resulting product was azeotropically distilled from the mixture. The lower phase of the resulting distillate was separated from the upper phase, was
5 washed with water, was treated with aqueous potassium hydroxide solution (53 g of 50%), and was then refluxed for one hour. A second azeotropic distillation and water washing yielded crude product which was further purified by distillation through a ten-plate perforated
10 column to provide the product ether (boiling range 82-84°C; 96.2% purity by GLC). The product identity was confirmed by GCMS and by ^1H and ^{19}F NMR.

Preparation of $\text{C}_5\text{F}_{11}\text{OC}_2\text{H}_5$

15 The title compound was prepared essentially as in Example 3 using anhydrous potassium fluoride (38.6 g, 0.67 mol), anhydrous diethylene glycol dimethyl ether (diglyme, 500 g), methyltrialkyl ($\text{C}_8\text{-C}_{10}$) ammonium chloride (Adogen™ 464,
20 available from Aldrich Chemical Company, 10.5 g), $\text{C}_4\text{F}_9\text{COF}$ (260 g of 60.7% purity, 0.59 mol), and diethyl sulfate (102.4 g, 0.67 mol). The reaction mixture was stirred at room temperature overnight, and then the resulting product was azeotropically distilled from the
25 reaction mixture. The lower product phase of the resulting distillate was separated from the upper phase and was treated with approximately 50 g of 50% aqueous potassium hydroxide, was refluxed for four hours, and was stirred at room temperature overnight. A second
30 azeotropic distillation and water washing gave crude product which was further purified by distillation

through a ten-plate perforated column to provide the product ether (boiling point 96°C; 99.6% purity by GLC). The product identity was confirmed by GCMS and by ^1H and ^{19}F NMR.

5

Solvency Properties

A number of potential solvents were tested for their ability to dissolve hydrocarbons of increasing molecular weight according to the procedure described
10 in U.S. Patent No. 5,275,669 (Van Der Puy et al.), the description of which is incorporated herein by reference. The data shown in Table 1 were obtained by determining the largest normal hydrocarbon alkane which was soluble in a particular solvent at a level of 50
15 percent by volume. The numbers in the Table correspond with the carbon number of the largest alkane, e.g., "8" refers to octane. Measurements were made from room temperature up to the boiling point of the solvent. For comparative purposes, hydrofluorocarbons (HFCs) and
20 perfluorocarbons (PFCs) were also tested using this method.







Table 1

Temperature (°C)	C ₄ F ₉ OCH ₃	C ₄ F ₉ OC ₂ H ₅	c-C ₆ F ₁₁ OCH ₃	CF ₃ CFHCFHC ₂ F ₅	C ₆ F ₁₄	C ₈ F ₁₈	C ₅ F ₁₁ H	C ₆ F ₁₃ H
23	9	12	10	7	6	5	7	7
30	10	12	11	7				
40	10	13	11	8	6	6	8	8
50	12	14	13	8	7	6		8
55	12	15	13	9				
60	12	15	13		7	7		9
73		17	15			7		10
101			18			9		

The data in Table 1 show that hydrocarbon alkanes are significantly more soluble in the alkoxy-substituted perfluorocompounds used in the cleaning process of this invention than in the comparative compounds, the HFCs and PFCs. This improved solvency was more pronounced at elevated temperatures. Thus, the cleaning process of the invention can be used to remove higher molecular weight hydrocarbons (e.g., oils, and greases) from substrate surfaces than can be removed using HFCs or PFCs. The higher solvency of the alkoxy-substituted perfluorocompounds for hydrocarbon alkanes indicates that these perfluorocompounds can serve not only as superior cleaning solvents for removing hydrocarbon soils, but can also be effective as solvents for depositing hydrocarbon coatings, e.g., coatings of lubricant, onto substrate surfaces.

Using essentially the above-described method, the solvency properties of other alkoxy-substituted perfluorocompounds were tested at room temperature. The compounds tested and the results obtained are shown in Table 2 below.

Table 2

Compound	Largest Soluble
	9
	11
$C_8F_{17}OCH_3$	6
$(CF_3)_2CFCF_2OCH_3$	9
$C_2F_5CF(OCH_3)CF(CF_3)_2$	8
$CF_3CF(OCH_3)CF(CF_3)_2$	9
$C_3F_7OCH_3$	10
$C_5F_{11}OCH_3$	8
$C_5F_{11}OC_2H_5$	10
	8
	7
	9
	8

Examples 8-10 and Comparative Examples A-C

In the following Examples and Comparative
 5 Examples, the cleaning ability of the alkoxy-
 substituted perfluorocompounds used in the cleaning

process of the invention was further evaluated. A
1.28 cm x 1.28 cm x 0.225 cm wire-wrapped, aluminum
coupon was coated with white heavy mineral oil
(available from Aldrich Chemical) by immersing the
5 coupon in an oil-filled beaker. The initial amount of
the oil on the coupon was determined by weighing it on
an analytical balance to the nearest 0.1 mg. The
coupon was immersed in a container of solvent and
sonicated for 1 minute at the indicated temperature
10 (see Table 3 below for the solvents and temperatures
used). The coupon was then weighed again, and the
results were recorded in Table 3 as percent oil
removal.

Table 3

Example	8	9	10	Comparative A	Comparative B	Comparative C
Temp. (°C)	C ₄ F ₉ OCH ₃	C ₄ F ₉ OC ₂ H ₅	c-C ₆ F ₁₁ OCH ₃	C ₆ F ₁₄	C ₆ F ₁₃ H	CF ₂ ClCFCl ₂
23	60.3	56.0	74.4	54.9	71.7	98.9
50	98.7	99.2	96.5	67.6	86.8	98.7
60	99.9	100.0	99.8			

The data in Table 3 show that the alkoxy-substituted perfluorocompounds removed amounts of the mineral oil which were comparable to the amounts removed by the comparative PFC and HFC compounds at room temperature. At elevated temperature, the cleaning properties of the perfluorocompounds were superior to those of the PFC and HFC compounds and equivalent to those of the comparative CFC compound.

10 Examples 11-13

Using essentially the same procedure as that described in Examples 8-10, the ability of the alkoxy-substituted perfluorocompounds to remove a fluorinated oil was evaluated. As in the previous Examples, a coupon was immersed in Krytox™ 157FSM perfluoropolyether oil having carboxylic acid end groups (available from DuPont), and the percent oil remaining after immersion in the solvent (at room temperature) was determined. The results are shown in Table 4 below.

Table 4

Example	11	12	13
Compound	$C_4F_9OCH_3$	$C_4F_9OC_2H_5$	$C-C_6F_{11}OCH_3$
% Removed	99.1	99.3	96.5

25 The data show that the alkoxy-substituted perfluorocompounds very effectively removed the perfluoropolyether oil from the surface of the coupon. This indicates that the perfluorocompounds can function

well as cleaning solvents for the removal of halogenated compounds such as halogenated oils and greases.

Examples 14-16 and Comparative Examples D-E

5 The ability of alkoxy-substituted perfluorocompounds to function as a rinse agent in a co-solvent cleaning process was evaluated. The above-described aluminum coupon was coated with solder flux (available from Alpha Metals as Alpha 611 rosin, mildly activated flux) 10 by immersing the coupon into a flux-filled beaker. The flux-coated coupon was then dried using a forced air convection drier. The initial amount of the flux on the coupon was determined by weighing it on an analytical balance to the nearest 0.1 mg. The coupon 15 was immersed in a container of a mixed solvating agent comprising approximately 50% methyl decanoate and 50% dipropylene glycol di-n-butyl ether and was sonicated for 1 minute at approximately 55°C. The coupon was then immersed for 30 seconds into alkoxy-substituted 20 perfluorocompound which had been heated to its boiling point. The coupon was weighed again, and the results were recorded in Table 5 below as percent oil removed from the coupon.

25

Table 5

Example	14	15	16	Comparative D	Comparative E
Compound	C ₄ F ₉ OCH ₃	C ₄ F ₉ OC ₂ H ₅	c-C ₆ F ₁₁ OCH ₃	C ₆ F ₁₄	C ₆ F ₁₃ H
% Removed	100.0	100.0	100.0	51.9	91.2

The data in Table 5 show that the alkoxy-substituted perfluorocompounds (used according to the cleaning process of the invention) effectively removed the solvating agent and flux residues, showing solvency properties superior to those of the comparative PFC and HFC compounds.

Examples 17-18 and Comparative Example F

The above-described aluminum coupon was dipped into Brayco 815Z perfluoropolyether oil (available from Castrol Inc., molecular weight of about 10,000) and then immersed in alkoxy-substituted perfluorocompound vapor (over the boiling liquid) for 60 seconds. The percent oil removal was determined in the above-described manner. The results are shown in Table 6.

Table 6

	17	18	Comparative F
Compound	$C_4F_9OCH_3$	$C_4F_9OC_2H_5$	C_6F_{14}
Percent Soil Removed	89.9%	93.3%	92.9%

Examples 19-20 and Comparative Example G

The above-described test coupon was dipped into a paraffinic oil comprising a mixture of linear and branched hydrocarbons (DuoSeal Pump Oil, available from Sargent Welch), was immersed in mixed solvating agent comprising approximately 50% methyl caproate and 50% dipropylene glycol di-n-butyl ether for 30 seconds, and was then rinsed in boiling alkoxy-substituted

perfluorocompound for 30 seconds. The percent oil removal was determined in the above-described manner. The results are shown in Table 7.

5

Table 7

	19	20	Comparative G
Compound	$C_4F_9OCH_3$	$C_4F_9OC_2H_5$	C_6F_{14}
Percent Soil Removed	99.8%	100.0%	89.2%

Examples 21-22

The above-described test coupon was dipped in white heavy mineral oil (available from Aldrich Chemical), was immersed in a boiling single-phase mixture of 40 volume % of a solvating agent comprising essentially methyl decanoate and 60 volume % of alkoxy-substituted perfluorocompound (a cleaning composition of the invention) for 60 seconds, was cooled for 60 seconds, and was then immersed in mixture vapor for 30 seconds. The percent oil removal was determined in the above-described manner. The results are shown in Table 8.

20

Table 8

	21	22
Fluorinated Component of Cleaning Composition	$C_4F_9OCH_3$	$C_4F_9OC_2H_5$
Percent Soil Removed	94.61%	94.28%

Examples 23-24 and Comparative Example H

The above-described test coupon was dipped into DuoSeal Pump Oil (available from Sargent-Welch), was immersed in a boiling mixture of 40 volume % of a solvating agent comprising mixed terpenes having a boiling range of 243-274°C and 60 volume % of alkoxy-substituted perfluorocompound (a cleaning composition of the invention), was cooled for 60 seconds, and was then immersed in mixture vapor for 30 seconds. The percent oil removal was determined in the above-described manner. The results are shown in Table 9.

Table 9

	23	24	Comparative H
Fluorinated Component of Cleaning Composition	$C_4F_9OCH_3$	$C_4F_9OC_2H_5$	C_6F_{14}
Percent Soil Removed	86.4%	99.4%	75.7%

15

Examples 25-26 and Comparative Example I

The above-described test coupon was dipped into DuoSeal Pump Oil (available from Sargent-Welch) and was then immersed in a mixture of 40 volume % n-C₆H₁₄ and 60 volume % alkoxy-substituted perfluorocompound (a cleaning composition of the invention) for 60 seconds at room temperature with ultrasonic agitation. The percent oil removal was determined in the above-described manner. The results are shown in Table 10.

25

Table 10

	25	26	Comparative I
Fluorinated Component of Cleaning Composition	$C_4F_9OCH_3$	$C_4F_9OC_2H_5$	C_6F_{14}
Percent Soil Removed	92.5%	99.0%	83.5%

Examples 27-28 and Comparative Example J

5 The above-described test coupon was dipped into DuoSeal Pump Oil (available from Sargent-Welch) and was then immersed in the vapor of a boiling mixture of 40 volume % n- C_6H_{14} and 60 volume % alkoxy-substituted perfluorocompound (a cleaning composition of the invention) for 60 seconds. The percent oil removal was determined in the above-described manner. The results are shown in Table 11.

Table 11

Example	27	28	Comparative J
Fluorinated Component of Cleaning Composition	$C_4F_9OCH_3$	$C_4F_9OC_2H_5$	C_6F_{14}
Percent Soil Removed	90.8%	97.1%	73.8%

15

 The results obtained in Examples 17-28 show that alkoxy-substituted perfluorocompounds are effective at removing a variety of contaminants from substrate surfaces.

20

In Examples 29 to 70 the process of cleaning textiles using alkoxy-substituted perfluoroalkanes was demonstrated. The cleaning compositions used were as follows:

Cleaning
composition

- | | |
|---|--|
| A | $C_4F_9OCH_3$ (neat) |
| B | $C_4F_9OC_2H_5$ (neat) |
| C | 0.5 wt.% $C_4F_9OC_2F_4OCF_2C(O)NHC_2H_4OH$, 0.2 wt.% Brij 30™ in $C_4F_9OCH_3$ |
| D | 0.5 wt.% $C_4F_9OC_2F_4OCF_2C(O)NHC_2H_4OH$, 0.2 wt.% Igepal CO-210™ in $C_4F_9OCH_3$ |
| E | 0.5 wt.% FC-171™, 0.2 wt.% TRITON X-15™, in $C_4F_9OCH_3$ |
| F | 0.5 wt.% FC-171™, 0.2 wt.% TRITON X-15™, in $C_4F_9OC_2H_5$ |

- 5 BRIJ 30™ is an ethoxylated (poly)ethylene oxide available from ICI Chemical
- IGEPAI CO-210™ is a nonylphenoxyethoxylate) is available from Rhone-Poulenc
- 10 TRITON X-15™ is an octylphenoxyethoxylate) is available from Union Carbide
- FC-171™ is a fluorinated sulfonamide surfactant available from 3M Company, St. Paul, MN
- $C_4F_9OC_2F_4OCF_2C(O)NHC_2H_4OH$ may be prepared by the method described in U.S. 5,125,978 (Flynn, et al.) and U.S.
- 15 5,089,152 (Flynn et al.)

In these Examples, fabric samples measuring about 15 x 15 cm and weighing about 10 grams were stained by adding three drops of mineral oil, and separately,

three drops of corn oil, to the fabric, covering the stain with wax paper, and applying a 500 g weight for about one minute to ensure oil penetration into the fabric. The samples were then allowed to stand for
5 about thirty minutes prior to each cleaning trial.

The stained fabrics were placed into individual quart glass jars with 200 mL of a cleaning solution, capped, and then shaken for ten minutes. The cleaning solution was then drained and the fabric samples rinsed
10 with 200 mL of the same neat alkoxy-substituted perfluoroalkane for five minutes, followed by air drying. The rinse step was omitted in Examples in which the neat fluorinated ether was used as the cleaning solution.

15 The fabric samples were evaluated visually comparing the size and appearance of the stain on the untreated fabric to that of the cleaned fabric. The stains were then evaluated with a Model CR-300™ Chromometer (Minolta Camera, Japan) to quantify the
20 color of the stain before and after cleaning. Results are tabulated in the Tables below, organized by the identity of the Oil and Fabric tested. In the tables, the value ΔE represents the difference in color measurements between a stained and an unstained portion
25 of the same fabric sample. In practice, a cleaned stain should have a Delta E value that is lower than an untreated (stained but not cleaned) sample.

Table 12

Example	Cleaning Solution	Oil	Fabric	ΔE	Visual Observation
29 Control	Untreated	Corn Oil	65/35 Polyester Cotton Twill	7.1 ± 0.04	
30	A	"	"	4.52 ± 0.04	Spot size decreased to 2/3
31	B	"	"	4.58 ± 0.06	Spot size decreased to 2/3
32	C	"	"	4.56 ± 0.00	Spot size decreased to 1/2
33	D	"	"	5.26 ± 0.04	Spot size decreased to 1/2
34	E	"	"	3.54 ± 0.12	Spot size decreased to less than 1/2
35	F	"	"	4.56 ± 0.23	Spot size decreased to less than 1/4

Table 13

Example	Cleaning Solution	Oil	Fabric	ΔE	Visual Observation
36 Control	Untreated	Corn Oil	100% Cotton style 400	0.27 ± 0.03	
37	A	"	"	1.86 ± 0.30	Spot size decreased to 1/2
38	B	"	"	2.6 ± 0.04	Spot size decreased to 1/4
39	C	"	"	0.39 ± 0.07	Spot size decreased to less than 1/2
40	D	"	"	0.34 ± 0.06	Spot size nearly gone
41	E	"	"	0.88 ± 0.01	Spot size decreased to 1/2
42	F	"	"	0.76 ± 0.05	Spot size decreased to 1/4

Table 14

Example	Cleaning Solution	Oil	Fabric	ΔE	Visual Observation
43 Control	Untreated	Corn Oil	100 % Wool	11.41 ± 0.75	
44	A	"	"	10.46 ± 0.13	No Change
45	B	"	"	8.87 ± 0.07	No Change
46	C	"	"	8.96 ± 0.16	No Change
47	D	"	"	9.78 ± 0.08	No Change
48	E	"	"	8.74 ± 0.22	No Change
49	F	"	"	8.54 ± 0.06	No Change

Table 15

Example	Cleaning Solution	Oil	Fabric	ΔE	Visual Observation
50 Control	Untreated	Light Mineral Oil	65/35 Polyester Cotton Twill	5.80 ± 0.03	
51	A	"	"	0.50 ± 0.07	Spot not visible
52	B	"	"	0.14 ± 0.16	Spot not visible
53	C	"	"	0.44 ± 0.04	Spot not visible
54	D	"	"	0.36 ± 0.06	Spot not visible
55	E	"	"	0.44 ± 0.19	Spot not visible
56	F	"	"	0.20 ± 0.05	Spot not visible

Table 16

Example	Cleaning Solution	Oil	Fabric	ΔE	Visual Observation
57 Control	Untreated	Heavy Mineral Oil	100% Cotton style 400	0.40 ± 0.06	
58	A	"	"	0.37 ± 0.28	Not visible
59	B	"	"	0.13 ± 0.08	Not visible
60	C	"	"	0.22 ± 0.04	Not visible
61	D	"	"	0.17 ± 0.06	Not visible
62	E	"	"	0.15 ± 0.01	Not visible
63	F	"	"	1.20 ± 0.08	Not visible

Table 17

Example	Cleaning Solution	Oil	Fabric	ΔE	Visual Observation
64 Control	Untreated	Heavy Mineral Oil	100% Wool	8.58 ± 0.33	
65	A	"	"	0.76 ± 0.16	Faintly visible
66	B	"	"	0.84 ± 0.13	Faintly visible
67	C	"	"	0.67 ± 0.10	Faintly visible
68	D	"	"	0.39 ± 0.01	Not visible
69	E	"	"	0.57 ± 0.21	Not visible
70	F	"	"	0.79 ± 0.04	Not visible

As can be seen in the above Tables, the mineral oil stains were essentially completely removed with all cleaning solutions, based on both visual and colorimetric analysis. The corn oil stains remained to some degree on all fabrics. The polyester/cotton samples showed a decrease in stain size (diameter) and a lighter (less color) stain than with the untreated control, but addition of a surfactant to the alkoxy-substituted perfluoroalkane was more effective in reducing the size and color of the stain. On the 100% cotton samples, the neat alkoxy-substituted perfluoroalkane reduced the size of the stain, but made the stain darker by the colorimetric measurements.

Various modifications and alterations of this invention will be apparent to those skilled in the art without departing from the scope and spirit of this invention.

We claim:

1. A dry cleaning process for removing
contaminants from the surface of a fabric substrate,
5 the process comprising the step of contacting a fabric
substrate with a liquid- and/or vapor-phase cleaning
composition comprising at least one mono-, di-, or
trialkoxo-substituted perfluoroalkane,
perfluorocycloalkane, perfluorocycloalkyl-containing
10 perfluoroalkane, or perfluorocycloalkylene-containing
perfluoroalkane compound, said compound optionally
containing one or more additional catenary heteroatoms.

2. The process of Claim 1 wherein said compound
15 has a boiling point in the range of from about 25°C to
about 200°C.

3. The process of Claim 1 wherein said compound
is represented by the general formula

20



wherein x is an integer of 1 to 3; when x is 1, R_f is
selected from the group consisting of linear or
25 branched perfluoroalkyl groups having from 2 to about
15 carbon atoms, perfluorocycloalkyl-containing
perfluoroalkyl groups having from 5 to about 15 carbon
atoms, and perfluorocycloalkyl groups having from 3 to
about 12 carbon atoms; when x is 2, R_f is selected from
30 the group consisting of linear or branched

perfluoroalkanediyl groups or perfluoroalkylidene groups having from 2 to about 15 carbon atoms, perfluorocycloalkyl- or perfluorocycloalkylene-containing perfluoroalkanediyl or perfluoroalkylidene groups having from 6 to about 15 carbon atoms, and perfluorocycloalkanediyl groups or perfluorocycloalkylidene groups having from 3 to about 12 carbon atoms; when x is 3, R_f is selected from the group consisting of linear or branched perfluoroalkanetriyl groups having from 2 to about 15 carbon atoms, perfluorocycloalkyl- or perfluorocycloalkylene-containing perfluoroalkanetriyl groups having from 6 to about 15 carbon atoms, and perfluorocycloalkanetriyl groups having from 3 to about 12 carbon atoms; each R_h is independently selected from the group consisting of linear or branched alkyl groups having from 1 to about 8 carbon atoms, cycloalkyl-containing alkyl groups having from 4 to about 8 carbon atoms, and cycloalkyl groups having from 3 to about 8 carbon atoms; wherein either or both of the groups R_f and R_h can contain one or more catenary heteroatoms; and wherein the sum of the number of carbon atoms in R_f and the number of carbon atoms in R_h is greater than or equal to 4.

25

4. The process of Claim 3 wherein x is 1; R_h is an alkyl group having from 1 to about 6 carbon atoms; and R_f but not R_h can contain one or more catenary heteroatoms.

30

5. The process of Claim 4 wherein R_f is selected from the group consisting of linear or branched perfluoroalkyl groups having from 3 to about 6 carbon atoms, perfluorocycloalkyl-containing
5 perfluoroalkyl groups having from 5 to about 8 carbon atoms, and perfluorocycloalkyl groups having from 5 to about 6 carbon atoms; and R_h is an alkyl group having from 1 to about 3 carbon atoms.




10 6. The process of claim 1, wherein the cleaning composition further comprises surfactant.

7. The process of claim 6, wherein the surfactant comprises a nonionic surfactant chosen from
15 the group consisting of an ethoxylated alcohol, an ethoxylated alkylphenol, an ethoxylated fatty acid, an alkylaryl sulfonate, a glycerol ester, an ethoxylated fluoroalcohol, a fluorinated sulfonamide, and mixtures thereof.

20

8. The process of claim 6, wherein the cleaning composition comprises from about 0.1 to about 5 percent by weight surfactant.

9. A dry cleaning process for removing
contaminants from the surface of a fabric substrate,
the process comprising the step of contacting a fabric
substrate with a liquid- and/or vapor-phase cleaning
5 composition comprising at least one compound selected
from the group consisting of $c\text{-C}_6\text{F}_{11}\text{CF}_2\text{OC}_2\text{H}_5$,
 $c\text{-C}_6\text{F}_{11}\text{CF}_2\text{OCH}_3$, $4\text{-CF}_3\text{-}c\text{-C}_6\text{F}_{10}\text{CF}_2\text{OCH}_3$,



$\text{CH}_3\text{OCF}_2\text{-}c\text{-C}_6\text{F}_{10}\text{CF}_2\text{OCH}_3$, $\text{C}_4\text{F}_9\text{OC}_2\text{H}_5$,
 $\text{C}_4\text{F}_9\text{OCH}_3$, $c\text{-C}_6\text{F}_{11}\text{OCH}_3$, $(\text{CF}_3)_2\text{CFCF}_2\text{OCH}_3$, $(\text{CF}_3)_2\text{CFCF}_2\text{OC}_2\text{H}_5$,
 $\text{C}_8\text{F}_{17}\text{OCH}_3$, $\text{C}_2\text{F}_5\text{CF}(\text{OCH}_3)\text{CF}(\text{CF}_3)_2$, $\text{CF}_3\text{CF}(\text{OCH}_3)\text{CF}(\text{CF}_3)_2$,
 $\text{C}_5\text{F}_{11}\text{OCH}_3$, $\text{C}_5\text{F}_{11}\text{OC}_2\text{H}_5$, and $\text{C}_3\text{F}_7\text{OCH}_3$.

10. The process of claim 9, wherein the
cleaning composition further comprises surfactant.

11. The process of claim 10, wherein the
20 surfactant comprises a nonionic surfactant chosen from
the group consisting of an ethoxylated alcohol, an
ethoxylated alkylphenol, an ethoxylated fatty acid, an
alkylaryl sulfonate, a glycerol ester, an ethoxylated
fluoroalcohol, a fluorinated sulfonamide, and mixtures
25 thereof.


12. The process of claim 10, wherein the cleaning composition comprises from about 0.1 to about 5 percent by weight surfactant.

5

13. A cleaning composition comprising (a) a major amount of at least one mono-, di-, or trialkoxy-substituted perfluoroalkane, perfluorocycloalkane, perfluorocycloalkyl-containing perfluoroalkane, or
10 perfluorocycloalkylene-containing perfluoroalkane compound, said compound optionally containing one or more additional catenary heteroatoms; and (b) surfactant.

14. The composition of Claim 13, wherein said
15 compound has a boiling point in the range of from about 25°C to about 200°C.

15. The composition of Claim 13, wherein said
20 compound is represented by the general formula



wherein x is an integer of 1 to 3; when x is 1, R_f is
25 selected from the group consisting of linear or branched perfluoroalkyl groups having from 2 to about 15 carbon atoms, perfluorocycloalkyl-containing perfluoroalkyl groups having from 5 to about 15 carbon atoms, and perfluorocycloalkyl groups having from 3 to
30 about 12 carbon atoms; when x is 2, R_f is selected from

the group consisting of linear or branched perfluoroalkanediyl groups or perfluoroalkylidene groups having from 2 to about 15 carbon atoms, perfluorocycloalkyl- or perfluorocycloalkylene-
5 containing perfluoroalkanediyl or perfluoroalkylidene groups having from 6 to about 15 carbon atoms, and perfluorocycloalkanediyl groups or perfluorocycloalkylidene groups having from 3 to about 12 carbon atoms; when x is 3, R_f is selected from the
10 group consisting of linear or branched perfluoroalkanetriyl groups having from 2 to about 15 carbon atoms, perfluorocycloalkyl- or perfluorocycloalkylene-containing perfluoroalkanetriyl groups having from 6 to about 15 carbon atoms, and
15 perfluorocycloalkanetriyl groups having from 3 to about 12 carbon atoms; each R_h is independently selected from the group consisting of linear or branched alkyl groups having from 1 to about 8 carbon atoms, cycloalkyl- containing alkyl groups having from 4 to about 8 carbon
20 atoms, and cycloalkyl groups having from 3 to about 8 carbon atoms; wherein either or both of the groups R_f and R_h can contain one or more catenary heteroatoms; and wherein the sum of the number of carbon atoms in R_f and the number of carbon atoms in R_h is greater than or
25 equal to 4.




16. The composition of claim 13, wherein the surfactant comprises a nonionic surfactant.

17. The composition of claim 16, wherein the nonionic surfactant is selected from the group consisting of an ethoxylated alcohol, an ethoxylated alkylphenol, an ethoxylated fatty acids, an alkylaryl sulfonate, a glycerol ester, an ethoxylated fluoroalcohol, a fluorinated sulfonamide, and mixtures thereof.

18. The composition of claim 13, wherein the composition comprises from about 0.1 to about 5 percent by weight surfactant.

19. A composition comprising (a) a major amount of at least one compound selected from the group consisting of

$c-C_6F_{11}CF_2OC_2H_5$, $c-C_6F_{11}CF_2OCH_3$, $4-CF_3-c-C_6F_{10}CF_2OCH_3$,



$CH_3OCF_2-c-C_6F_{10}CF_2OCH_3$, $C_4F_9OC_2H_5$, $C_4F_9OCH_3$, $c-C_6F_{11}OCH_3$, $(CF_3)_2CFCF_2OCH_3$, $(CF_3)_2CFCF_2OC_2H_5$, $C_8F_{17}OCH_3$, $C_2F_5CF(OCH_3)CF(CF_3)_2$, $CF_3CF(OCH_3)CF(CF_3)_2$, $C_5F_{11}OCH_3$, $C_5F_{11}OC_2H_5$, and $C_3F_7OCH_3$; and (b) surfactant.

20. The composition of claim 19, wherein the surfactant comprises a nonionic surfactant.

21. The composition of claim 20, wherein the
5 nonionic surfactant is selected from the group
consisting of an ethoxylated alcohol, an ethoxylated
alkylphenol, an ethoxylated fatty acids, an alkylaryl
sulfonate, a glycerol ester, an ethoxylated
fluoroalcohol, a fluorinated sulfonamide, and mixtures
10 thereof.

22. The composition of claim 19, wherein the
composition comprises from about 0.1 to about 5 percent
by weight surfactant.

15

23. A process for removing contaminants from a
substrate comprising the steps of contacting a
substrate with a liquid- and/or vapor-phase cleaning
composition comprising (a) at least one mono-, di-, or
20 trialkyloxy-substituted perfluoroalkane,
perfluorocycloalkane, perfluorocycloalkyl-containing
perfluoroalkane, or perfluorocycloalkylene-containing
perfluoroalkane compound, said compound optionally
containing one or more additional catenary heteroatoms;
25 and (b) surfactant.

INTERNATIONAL SEARCH REPORT

International Application No
PC1/US 96/07157

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 C11D7/50 D06L1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 C11D C07D C07C D06L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	DATABASE WPI Section Ch, Week 9650 Derwent Publications Ltd., London, GB; Class D25, AN 96-503018 XP002029482 & JP 08 259 995 A (AGENCY OF IND SCI & TECHNOLOGY), 8 October 1996 see abstract	1-5,23
A	--- EP 0 450 855 A (ICI PLC) 9 October 1991 cited in the application see claims	1,2,23
A	--- WO 93 09272 A (ALLIED SIGNAL INC) 13 May 1993 see page 16, line 20 - page 17, line 14; claims --- -/--	1,2,23

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

15 April 1997

Date of mailing of the international search report

23.04.97

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Grittern, A

INTERNATIONAL SEARCH REPORT

International Application No
PC 1/US 96/07157

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 854 871 A (EANZEL A) 17 December 1974 see claims ---	1,2,23
A	DATABASE WPI Section Ch, Week 9117 Derwent Publications Ltd., London, GB; Class B03, AN 91-123600 XP002003769 & SU 1 427 780 A (NOVOS ORG CHEM INST) , 15 September 1990 see abstract -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PC1/US 96/07157

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0450855 A	09-10-91	AU 640760 B	02-09-93
		AU 7391391 A	10-10-91
		CA 2039828 A	05-10-91
		JP 5271692 A	19-10-93
		NZ 237628 A	26-07-94

WO 9309272 A	13-05-93	US 5273592 A	28-12-93
		AU 2906892 A	07-06-93

US 3854871 A	17-12-74	US 3920389 A	18-11-75
